Technical Data Sheet

LEVANYL®
Violet BN-LF

Colour Index	Part I Part II	Pigment Violet 23 51319
Composition	aqueous, solvent free, organic pigment preparation	
Safety data sheet	147633	
Form supplied	free-flowing paste suitable for pumping and metering	
Shade tolerance (CIElab)	DE max. 1.0	
Color strength tolerance	95.0 – 105.0%	
Density (23 °C)	1.00 – 1.30 g/cm^3	
Main fields of application	Paints & Coatings, paper coating, office supplies	
Further applications	phenolic resin, melamine resin, abrasive paper, technical laminate paper, synthetic leather (coagulatin), paper pulp, wallpaper colors, tissue printing inks, nonwoven, wood protection, wood stains, asphalt, latex, fertilizers, seed, shoe polishes, detergents and cleaning agents	
Storage stability	24 months from delivery ex plant LANXESS Deutschland GmbH	
Pigment content	approx. 27 %	
Dispersing agent	nonionic	
pH-Value	6.0 – 8.0 form supplied (according to DIN ISO 787-9)	
Viscosity (23 °C)	max. 1000 mPa s (D = 70 s^{-1}, DIN 53019)	

Notes on processing:
Always stir before use and close containers after use.

LANXESS Deutschland GmbH
Business Unit Rhein Chemie Additives
Kennedyplatz 1
50569 Cologne, Germany
http://rch.lanxess.com