


BAYSCRIPT® Black N liq.

General properties	Highly purified, low salt grade black dye mixture Very good filtration properties (0.45 µm) High color strength Can be shaded with red direct dyes for neutral black
Color Index Part I	Direct Black mixture
Color Index Part II	–
Chemical class	Disazo dyes
Appearance	Black liquid
Dye content	≈ 23%
Color strength tolerance	± 5%
Solvent	Water
Surface tension	> 50 mN/m
pH (form supplied)	8 – 9
Viscosity	< 10 mPas
Filterability (0.45 µm filter)	≤ 0.01% residue
Lightfastness	3
Solubility (g/L at 25 °C)	Water____miscible Glycols____miscible
Ion content (ppm)	Chloride < 500 Sulfate < 3000 Calcium < 40 Magnesium < 20 Silicon < 30 Iron < 20 Copper < 20
Applications	Water-based inks Thermal and piezo ink-jet printing Office supplies Fine liner inks, fountain-pen inks Writing instruments Especially suitable for industrial ink-jet printing & barcoding
Stability	Storage stability: 24 months from delivery ex plant. Protect from freezing. BAYSCRIPT® N liq. is stable against weak acids and bases.

Absorbance curve

BAYSCRIPT® Black N liq. in water



® = registered trade mark

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.



LANXESS Deutschland GmbH
Business Unit Rhein Chemie Additives
Kennedyplatz 1
50569 Cologne, Germany
<http://rch.lanxess.com>