# **Technical Data Sheet**



Rhenocure® IS 90-20

Specialty and standard chemicals

#### **Function**

Vulcanizing agent for natural and synthetic rubbers

## **Product description**

Composition: min. 78 % total sulfur

min. 70 % insoluble sulfur

max. 22 % oil

Density: approx. 1.6 g/cm<sup>3</sup>

Appearance: non-dusting yellow powder

Physiological properties: see safety data sheet

#### Use

Mode of action: Rhenocure IS 90-20 contains min. 70 % by weight of a modified polymeric

sulfur, which is insoluble in carbon disulfide and other solvents. Rhenocure IS 90-20 is a vulcanizing agent for all natural and synthetic rubber compounds in which it should be avoided that the sulphur blooms or infiltrates neighbouring

layers of compound. Therefore, the use of Rhenocure IS 90-20 is

recommended for all applications that require laying-up, welding or where

good ply adhesion is essential.

Processing: The oil coating guarantees non-dusting working conditions and quick

incorporation and dispersion in the rubber compound. In order to avoid the insoluble sulfur converting into soluble sulfur, Rhenocure IS 90-20 should only

be added towards the end of the mixing process.

Dosage: 1-5 phr

Application: All types of tires, conveyor belts, retreading material, assembled hoses, etc.

### **Packaging**

25 kg paper bags on 1000 kg skid

### Storage stability

In original closed containers under cool and dry conditions 365 days from date of production

#### Handling

For additional handling information on Rhenocure IS 90-20 please consult current safety data sheet.



Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and, therefore, entirely your own responsibility. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you. We will, of course, provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.



LANXESS Deutschland GmbH Business Unit Rhein Chemie Kennedyplatz 1 D-50569 Cologne, Germany http://rch.lanxess.com

Page

2 of 2

LANXESS
Business Unit

Edition: 18. Nov 2016 Revised: Printed on: 11-18-2016 08-10-2017