

## Rhenosin® FH 70

Plasticizers

---

### Function

Synthetic plasticizer for mixes based on natural and synthetic rubber

### Product description

Composition:	70 % aromatic polyether (Vulkanol® FH) 30 % silica filler
Appearance:	white non-dusting powder
Density, 20 °C:	approx. 1.25 g/cm <sup>3</sup>
Discolouration of vulcanizates:	none
Physiological properties:	see safety data sheet.

### Use

**Mode of action:** Rhenosin FH 70 increases the building tack of mixes based on synthetic rubber and improves processability. Rhenosin FH 70 has a good dispersing effect on carbon blacks and light colored reinforcing fillers. In general, it does not influence the storage stability and scorch tendency of mixes. Rhenosin FH 70 is the solidified form of the high viscosity Vulkanol FH. The product is easy to weigh and dose. It easily incorporates and disperses homogeneously in all rubber compounds.

Rhenosin FH 70 meets the requirements of the German legislation for foodstuffs (BfR Recommendation XXI, incl. Categ. 1) when used in rubber goods which come into contact with foodstuffs (dosage: max. 7 % calculated on the finished goods).

**Dosage:** In NR, NBR, CR, IIR up to 20 phr,  
in SBR 5-15 phr

**Application:** Technical rubber articles, e.g. conveyor belts, raw edge V-belts, roller covers, also in foodstuff quality

### Packing

25 kg carton on 600 kg skid

### Storage stability

In original closed containers under cool and dry conditions 730 days from date of production

## Handling

For additional handling information on Rhenosin FH 70 please consult current safety data sheet.

Vulkanol® is a registered trade mark of Lanxess AG

---

Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and, therefore, entirely your own responsibility. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you. We will, of course, provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.

---



**LANXESS Deutschland GmbH**  
**Business Unit Rhein Chemie**  
Kennedyplatz 1  
D-50569 Cologne, Germany  
<http://rch.lanxess.com>