

Vulkanol® 95

Plasticizers

Function

Plasticizer to improve the low-temperature flexibility of elastomer vulcanizates

Product description

Composition: Adipic diester

Appearance: slightly yellowish liquid

Typical characteristics:

Density, 25 °C (DIN 52004):	1.01-1.02 g/ml
Acid number:	max. 1 mg KOH/g
Refractive index:	1.44-1.45

Use

Mode of action: Vulkanol® 95 is a special plasticizer compatible with many elastomers. Its flexibilizing effect at low temperatures and its low vapor pressure at high temperatures make Vulkanol® 95 the plasticizer of choice in rubber articles over a wide range of temperatures. Vulkanol® 95 is easily dispersible and affects the physical properties of rubber compounds only slightly. Vulkanol® 95 is compatible with CR, NBR, NR, SBR, ECO, EPDM, IIR.

Processing: Vulkanol® 95 is incorporated with the fillers.

Dosage:

NBR, PUR, ECO:	max 30 phr
ACM:	max 25 phr
EPM, EPDM, polysulfide rubber:	max 15 phr
CR, NR, SBR:	max 10 phr
IIR:	max 5 phr

Application: Refrigerator seals, hoses, ribbons, raw edge V-belts, gas meter membranes

Packing

190 kg plastic drums on 760 kg skids

Storage stability

In original sealed containers under cool and dry conditions 1095 days from date of production

Handling

For additional handling information on Vulkanol[®] 95 please consult current safety data sheet.

Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and, therefore, entirely your own responsibility. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you. We will, of course, provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.



LANXESS Deutschland GmbH
Business Unit Rhein Chemie
Kennedyplatz 1
D-50569 Cologne, Germany
<http://rch.lanxess.com>