

LEVAPLAST® Green 7 O-LF

Colour Index	Part I Pigment Green 7 Part II 74260
Composition	Phthalate-free plasticiser based pigment dispersion
Form supplied	paste - like pumpable dispersion
Shade tolerance (CIElab)	DE max. 1.0
Color strength tolerance	95.0 – 105.0%
Main fields of application	many types of polymers including PVC, polyurethanes and rubber
Further applications	Polyvinylchloride , Rubber, Phenolic Resins, Polyurethane elastomers, foams, Thermoplastics, adhesives and sealants, Vinyl wallpapers, Floor coverings, Cable isolations and sheathings, Films, Artificial Leather, Textile Coverings
Storage stability	6 months from delivery ex plant LANXESS Deutschland GmbH
Pigment content	approx. 28%
Water content (DIN 51777)	max. 0,1%
Dispersing agent	phthalate-free plasticiser
Viscosity (23 °C)	max. 3000 mPas (D = 29 s ⁻¹) DIN 53019

Notes on progressing

Always stir before use and close containers after use



This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.



LANXESS Deutschland GmbH
Business Unit Rhein Chemie Additives
Kennedyplatz 1
50569 Cologne, Germany
<http://rch.lanxess.com>

